Chameleon Sharp Wall Acoustics Specifications





1

Colours

The 9 mm PET felt from Chameleon Sharp Wall Acoustics is dyed-through. We have selected 21 colors, with a strong representation in shades of gray and brown.



White P001



Dusty white P002

Flat white

P007



Black lava P006





Rust P011





Dusk P016



Tree bark P012



Pink rose P017



White marble P003



Hare P008





Calm grey P004



Canyon P009





Rough grey P005

Light blue quartz P015



Ocean green P020



Anthracite P021







Magma P013



Garnet P018




Polarice P014

lguana P019

Designs

As standard, the panel is produced without a pattern. Optionally, you can choose from four V-groove patterns, which are cut into the PET felt to enhance the aesthetic value of the panel.






All	

A10

A12



A13

AIS	


General

Size (cm)	Art. nr.	Cut-out code (optional)	Number of panels	Gross weight	Net weight
198 x 59 cm	11210.201*	A09, A10, A11, A12, A13	2	11,34 KG	9,00 KG
198 x 118 cm	11210.202 *	A09, A10, A11, A12, A13	3	17,01 KG	13,50 KG
198 x 98 cm	11210.203 *	A09, A10, A11, A12, A13	4	22,68 KG	18,00 KG
198 x 48 cm	11210.204*	A09, A10, A11, A12, A13	5	28,08 KG	22,50 KG

* When requesting a quote or placing an order, please include the article number followed by the color code of the PET felt, optionally followed by the cut-out code: [article number + color code + cut-out code (optional)].

Technical

Properties:	Acoustic
Material:	100% recyclable PET felt (of which 60% recycled)
Material thickness:	9 mm
Acoustic values:	Directly to the wall: αw 0,25 / SAA 0,30 50 mm air gap: αw 0,55 / SAA 0,70 100 mm air gap: αw 0,75 / SAA 0,76
Fire resistance:	Tested according to EN13501: B-s1, d0
Installation:	Adhesive (not included). For walls with a smooth texture: 51505.014. For walls with a rough texture: 51505.007.
Warranty:	2 years
Optional V-cut pattern:	3 mm deep, ± 6 mm wide
Edge finishing:	Bevel-cut edge, 3 mm



Packaging

Туре:	Schink foil
Contents:	Chameleon Sharp Wall Acoustics panel and assembly manual
Packaging unit:	l unit per panel
Materials:	Individual pieces: shrink film, corrugated cardboard, EPS bumper Large orders: bulk on pallet
Dimensions per unit:	Panel dimensions + 4 cm all around. Total thickness: approximately 3 cm.

Smit Visual B.V. Spaarpot 120-122 5667 KZ Geldrop The Netherlands T +31(0)40 - 280 85 00 F +31(0)40 - 286 76 15 E info@smit-visual.nl W chameleonwriting.com



